



GOVERNING EQUATIONS FOR CLASSICAL ELECTROMAGNETICS

	Integral Form	Differential Form	Name
Time-Domain	$Q_e(t) = \oiint_S \vec{D}(t) \cdot d\vec{s} = \iiint_V \rho_v(t) dv$	$\nabla \cdot \vec{D}(t) = \rho_v(t)$	Gauss' Law
	$\oiint_S \vec{B}(t) \cdot d\vec{s} = 0$	$\nabla \cdot \vec{B}(t) = 0$	No Magnetic Charge
	$V_{emf}(t) = \oint_L \vec{E}(t) \cdot d\vec{\ell} = - \iint_S \left[\frac{\partial \vec{B}(t)}{\partial t} \right] \cdot d\vec{s}$	$\nabla \times \vec{E}(t) = - \frac{\partial \vec{B}(t)}{\partial t}$	Faraday's Law
	$I(t) = \oint_L \vec{H}(t) \cdot d\vec{\ell} = \iint_S \left[\vec{J}(t) + \frac{\partial \vec{D}(t)}{\partial t} \right] \cdot d\vec{s}$	$\nabla \times \vec{H}(t) = \vec{J}(t) + \frac{\partial \vec{D}(t)}{\partial t}$	Ampere's Circuit Law
	$\oiint_S \vec{J} \cdot d\vec{s} = - \frac{\partial Q_e}{\partial t}$	$\nabla \cdot \vec{J} = - \frac{\partial \rho_v}{\partial t}$	Continuity of Current
	$\vec{D}(t) = [\epsilon(t)] * \vec{E}(t)$ $\vec{B}(t) = [\mu(t)] * \vec{H}(t)$	Electric Response Magnetic Response	Constitutive Relations
Frequency-Domain	$Q_e = \oiint_S \vec{D} \cdot d\vec{s} = \iiint_V \rho_v dv$	$\nabla \cdot \vec{D} = \rho_v$	Gauss' Law
	$\oiint_S \vec{B} \cdot d\vec{s} = 0$	$\nabla \cdot \vec{B} = 0$	No Magnetic Charge
	$V_{emf} = \oint_L \vec{E} \cdot d\vec{\ell} = - \iint_S [j\omega \vec{B}] \cdot d\vec{s}$	$\nabla \times \vec{E} = -j\omega \vec{B}$	Faraday's Law
	$I = \oint_L \vec{H} \cdot d\vec{\ell} = \iint_S [\vec{J} + j\omega \vec{D}] \cdot d\vec{s}$	$\nabla \times \vec{H} = \vec{J} + j\omega \vec{D}$	Ampere's Circuit Law
	$\oiint_S \vec{J} \cdot d\vec{s} = -j\omega Q_e$	$\nabla \cdot \vec{J} = -j\omega \rho_v$	Continuity of Current
	$\vec{D} = [\epsilon] \vec{E}$ $\vec{B} = [\mu] \vec{H}$	Electric Response Magnetic Response	Constitutive Relations

Parameter Definitions

- Electric Field Intensity, E (V/m)
- Electric Flux Density, D (C/m²)
- Magnetic Field Intensity, H (A/m)
- Magnetic Flux Density, B (Wb/m²)
- Electric Current Density, J (A/m²)
- Volume Charge Density, ρ_v (C/m³)
- Permittivity, ϵ (F/m)
- Permeability, μ (H/m)
- Electrical Conductivity, σ (1/ $\Omega \cdot m$)

Constants

- Permittivity: $[\epsilon] = \epsilon_0 [\epsilon_r]$
 $\epsilon_0 = 8.8541878176 \times 10^{-12}$ (F/m)
- Permeability: $[\mu] = \mu_0 [\mu_r]$
 $\mu_0 \approx 4\pi \times 10^{-7}$ (H/m)
 $\mu_0 = 1.2566370614 \times 10^{-6}$ (H/m)
- Impedance: $\eta_0 \approx 120\pi$ (Ω)
 $\eta_0 = 376.73031346177$ (Ω)
- Speed of Light: $c_0 = 299,792,458$ (m/s)

Lorentz Force Law

$$\vec{F} = q\vec{E} + q(\vec{v} \times \vec{B})$$

Sign Convention

e^{-jkz} For propagation in the +z direction.